

BINDER RAPIDA ESSICCAZIONE OPACO

Code	Binder	% by weight: Pigment/Binder
KJA.1620	KJA.1620	20 / 80

Description

1K Synthetic Fast Drying Matt Enamel.
 Good Coverage and Fast hardening, plus excellent resistance against weather conditions.
 It allows to achieve excellent finishes in industrial coatings.
 Realisable by mixing pigment and binder at the right mixing ratio.

Recommended for

Suitable for painting cycles of iron manufactures, external carpentry etc.

This kind of binder is not suitable for pure whites and bright colours in general.

Specific Weight Kg/Lt

1

VOC (g/Lt) product ready to use Dir. 2004/42/CE

IIA(I) (500)500

°Gloss

10-15

Application T°C

5-50

Pot-Life 20°C

N.A.

Colour Code



TUTTI I COLORI

Application

SPRAY


















Use graduated stick N.:

		10-25°C	25-35°C		By Vol.	By Weight	Vol. x Airles
	Product	KJA.1620	KJA.1620		5	100	6
	Hardener						
	Hardener						
	Thinner	RDL.P333	RDL.P333		1	20	1
	Viscosity (sF 4 20°C)				16-17	16-17	21-25

BINDER RAPIDA ESSICCAZIONE OPACO

Code
KJA.1620

Conventional				
	Gravity Feed	Suction Feed Spray	HVLP	Airless
				
	1,4-1,6	1,6-1,8	1,4-1,6	1140/1340
	3-4	4	0,7	48-144
	2-3	2-3	2	1+1/2
	10-15	10-15	10-15	10-15
	10	10	10	10
	18-24	18-24	18-24	18-24
	1	1	1	1
	20'X40	20'X40	20'X40	20'X40
	20-25	20-25	20-25	30-40
	50-70	50-70	50-70	50-70
	7-8	7-8	7-8	7-8

Sanding with Orbital
**Polishing**
**Overpaintable with...**

Max Time to overcoat at 20°C


Min Time to overpaint in 20°C



Store free from frost



Store in cool place



Protect from umidity



Use fresh air mask